

Forbo Floor Care: Allura Click Pro

Forbo Flooring Cleaning and Maintenance advice:

The Forbo Allura LVT vinyl collections are easy to clean and maintain, thanks to their highly durable PUR finish.

Allura Click Pro is occupancy ready on completion of the installation and initial cleaning.

Initial clean before use

Vacuum the floor to remove all loose debris, dirt and dust off the floor and clean the floor with a neutral floor cleaner. For larger areas, a scrubber dryer or a rotary machine (150-180 rpm) with a 3M red pad or equivalent may be used. Pick up dirty water with a wiper and mop or wet vacuum, rinse with clean water and allow floor to dry.

Regular cleaning

The frequency of regular cleaning method will depend on the amount of traffic, soiling levels, desired appearance, and hygiene standards.

- Remove dust and loose dirt by vacuum cleaning, sweeping or mopping*.
- Remove spots, stains and spillages with a damp mop* and a neutral floor cleaner.

As required:

- Spray clean the floor with a rotary machine (150-180 rpm), a 3M red pad or equivalent and neutral floor cleaner

Periodic maintenance

The following maintenance actions should be used when needed to maintain a satisfactory level of appearance.

- Remove dust and loose dirt by vacuum cleaning, sweeping or mopping*.
- Remove spots, stains and spillages with a damp mop* and a neutral floor cleaner.
- Spray buff the floor with a rotary machine (300-500 rpm) and a 3M red pad or equivalent using a buffable pH neutral floor maintainer to remove gloss irregularities and provide an even appearance.

Please note:

** For manual cleaning of Allura Click Pro, Forbo recommend flat microfibre mopping systems.*

** For all above methods, do not use excessive water when cleaning and remove cleaning water promptly*

Best Practice: Tips for effective floor care

General advice

Protect newly laid floors

All newly laid floors should be covered and protected from all other trades during the contract with a suitable non-staining protective covering.

Use protective feet on chairs and tables to reduce scratching. Castor wheels should be of soft material suitable for resilient floor coverings (according to EN425)

Use Entrance Systems

As much as 80% of dirt entering a building is brought in by foot traffic. Entrance flooring systems of an appropriate size (ideally more than 6lm) and quality should be used. Forbo Coral or Nuway entrance flooring systems, are independently proven to remove and retain up to 94% of all dirt and moisture entering a building by foot traffic; reducing maintenance costs and maximising appearance retention of adjacent flooring products as well as reducing slip risk. As with any dirt removal system all entrance flooring systems should be regularly cleaned to release the dirt which has been removed.

Cleaning

- Regular cleaning is more beneficial and cost effective than occasional deep cleaning.
- Use recommended cleaning products. High quality cleaning products and equipment ensure efficient maintenance and represent only a small proportion of maintenance costs.
- Always follow the manufacturer's instructions for cleaning products.
- Always follow the Health and Safety guidance provided.

Use of Floor Care Chemicals

The improper use of cleaning chemicals may cause damage and/or discolouration.

Overuse or inadequate rinsing of cleaning chemicals may compromise the performance of the floor.

Abrasive powders or cleansers should not be used. Do not use seals or polishes, or floor maintainers containing polish as the slip resistant properties of Allura Click Pro could be reduced.

Frequently Asked Questions

How often should I clean my floor?

The optimum frequency for cleaning and maintenance is determined by the way the floor is used. When producing a cleaning and maintenance schedule it is good practice to consider the situation of the floor first:

- Is it near an entrance to the building or on an upper floor?
- Will it collect dry or moist soil?
- What level of traffic will it be subjected to?
- Remember that light and uni-colours may need to be cleaned more frequently.

Can I polish my floor?

Polish should not be applied to any Forbo Allura product as the slip resistant properties may be adversely affected.

How do I remove stains?

Remove stains as soon as they are discovered. Most stains can be safely removed using a dry (paper) towel, water, detergent, white spirit or alcohol (in that order).

Do NOT use highly alkaline products (ammonia, soda) or strong solvents such as acetone as they can be harmful to both people and to your floor.

Marks caused by	Remove with
Chocolate, grease, egg, coffee, juice, etc.	Neutral floor cleaner in lukewarm water
Asphalt, oil, rubber, soot	Cleaners' white spirits
Chewing-gum	Cool with cold spray or ice cubes and scrape.
Rust	Oxalic or citric acid in lukewarm water

If any doubt exists test cleaning materials on a sample piece or in an inconspicuous area.

Cleaning pads, brushes, machine speeds and floor care products

Pad codes

The colour codes indicating grades of pads may vary depending on the manufacturer/country.

Task	3M Pad colour
For regular spray cleaning	Red
For periodic maintenance	Red

Note:

Brown or black pads should not be used. Care should be taken when considering enhanced abrasion pads to ensure suitability with the flooring.

Machine speeds

For machine cleaning and maintenance, 150 to 180rpm is recommended.

Recommended Floor care products

For regular and periodic cleaning use a pH neutral detergent such as M2 Care Ultra, a pH neutral anti-bacterial cleaning solution. The example products above are available from the Wrennalls Group. Please tel. 01772 435739 for further information.

Other floor care products may be used on Forbo Flooring resilient floor coverings. If alternative products are to be used consult with your regular supplier for more information and guidance.

Contact us:

Web: www.forbo-flooring.co.uk
 Email: info.flooring.uk@forbo.com
 Telephone: 0800 0282 162
 Fax: 01772 646912