








ARCHITEX

Textile backed luxury vinyl sheet flooring

The Architex luxury vinyl sheet collection features a selection of 18 wood, stone and abstract designs, created to enhance residential interiors. With a premium textile backing, Architex provides warmth and comfort underfoot with the added benefit of being durable and easy to clean. Available in 2, 3 and 4 metre roll widths, Architex is also loose lay meaning no adhesive is required.

Ideally suited for use in residential and light commercial applications.



	Gauge	ISO 24346 (EN 428)	3.5mm
	Wear Layer	ISO 24340 (EN 429)	0.35mm
	Roll Size	ISO 24341 (EN 426)	4m x 20-25m 3m x 20-25m 2m x 20-25m
	Total Weight	ISO 23997 (EN 430)	2150g/m ²
	General Performance	ISO 26986 (EN 653)	Conforms
	Use Area	ISO 10874 (EN 685)	 
	Acoustic Impact Sound Reduction	ISO 10140-3	≥19dB
	Resistance to Chemicals	ISO 26987 (EN 423)	Good
	Reaction to Fire	EN 13501-1	Class Bfl-S1
	Abrasion Resistance	EN 653	Group T
	Slip Resistance*	EN 13893 DIN 51130	Class DS (dry condition) R10
	Residual Indentation	ISO 24343-1 (EN 433)	≤0.2mm
	Dimensional Stability	ISO 23999 (EN 434)	≤0.40%
	Flexibility	ISO 24344 (EN 435)	(Method A) / Pass 20mm Ø
	Underfloor Heating Thermal Resistance	EN 12667	Suitable, max 27°C 0.0542m ² K/W 0.542 Tog
	Static Electrical Propensity	EN 1815	≤2.0kV Classified as 'antistatic'
	Light Fastness	ISO 105-B02	(Method 3) ≥6
	Castor Chair (continuous use)	ISO 4918 (EN 425)	Suitable
	Furniture Leg	ISO 16581 (EN 424)	Conforms
	VOC Emissions	Indoor Air Comfort GOLD FloorScore	Eurofins certified product Certified

Environmentally Preferable Flooring - Polyflor Architex achieves BRE Global A+ rating (Generic) in the Green Guide to Specification. It is 100% recyclable. Visit www.polyflor.com/sustainability.

PUR - Polyflor Architex features a high quality, cross-linked polyurethane reinforcement, UV cured to provide a low-cost, polish free maintenance regime for the lifetime of the flooring.

Hygiene - All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning regime is the most important defence against infection.

For information regarding handling and installation, adhesives, maintenance, applications, chemical resistance and product warranty, consult Polyflor Customer Technical Services on +44 (0)161 767 1912, or email tech@polyflor.com.

*For safety flooring with sustainable wet slip resistance, refer to Polysafe ranges.

The data presented is correct at the time of printing. For latest information, please visit our website polyflor.com.

Decoration and shade may vary slightly from the samples shown.

