

Forbo Environmental Data Sheet

| Product name | Tessera Cloudscape | | | |
|------------------------|--|--|--|--|
| Product description | Tessera Cloudscape features organic texture and is produced with premium polyamide 6. Cloudscape complies with all requirements of EN1307: Textile Floor Coverings – Classification of Pile Carpets. | | | |
| Manufacturing location | Bamber Bridge, United Kingdom | | | |
| Site accreditation | ISO14001, ISO 9001, OHSAS 18001, SA8000° | | | |



Our footprint - how it's made

| Independent assessment and rating | | | |
|---|--|--|--|
| ISO 9001 Quality Management System | | | |
| ISO 14001 Environmental Management System | | | |
| OHSAS 18001 Occupational Health and Safety Management | | | |
| Cloudscape is made in an SA8000® certified facility | | | |
| | | | |
| EPD by December 2018 | | | |
| | | | |

Your footsteps - how it performs

| Н | leal | lth | and | wel | I | bein | g |
|---|------|-----|-----|-----|---|------|---|
|---|------|-----|-----|-----|---|------|---|

| Impact sound reduction | 26dB |
|------------------------|--|
| AgBB/DiBt | Pass |
| CHPS 01350 | Tessera products comply to 01350 Indoor Air Quality Standard |
| Air quality | |

Installation

Recommended adhesives

Carpet tiles must be adhered using an all over tackifier adhesive system: Forbo Eurocol 542 Eurofix

Tack Plus, a **solvent free** release system, is recommended. Where periphery tiles are not constrained by fixtures e.g. walls, edge strips etc, it is recommended that such tiles are adhered using a permanent adhesive; Forbo Eurocol 540 Eurosafe Special, again a **solvent free** adhesive, is recommended.

Adhesives must be applied according to the manufacturer's instructions and it is essential that tackifier adhesives are allowed to dry to a tacky finish before laying the carpet tile. Failure to do so could result in a permanent nonrelease bond.

Where contribution to credits for BREEAM sections HEA2 and HEA9 are required then low emission adhesive Eurocol 542 Eurofix tack plus should be used. If a permanent bond is required, please use Eurocol 640 Eurostar special.



creating better environments

| | Appropriate care and mainter | ance is essential to longevity and | d appearance retention and is necessary to | | |
|--|--|---|--|--|--|
| | Appropriate care and maintenance is essential to longevity and appearance retention and is necessary to maintain product warranties. Refer to the clean and care instructions available from Forbo Flooring Systems. All Tessera products are suitable for cleaning using the Dry Fusion technique. Dry Fusion uses 95% less water than the normal system of cleaning, produces no waste product, uses non hazardous and biodegradable cleaning solutions and all packaging and materials within the Dry Fusion System can be recycled. | | | | |
| | | | | | |
| End of life | | | | | |
| | Products suitable for reuse, recycling, downcycling and waste to energy. Forbo Flooring Systems works with recycling companies to clean, reuse and recycle old carpet tiles in the UK. | | | | |
| Contribution to Green | Building Schemes | | | | |
| BREEAM | | | | | |
| BREEAM 2018 | Environmental Product Declaration (EPD) available by December 2018 | | | | |
| Ska scheme (RICS) | | | | | |
| M12 soft floor covering criteria | (Ska Offices Vs 1.2 2013) Meets | (Ska Retail Vs 1.0 2012) Meets | (Ska Higher Education Vs 1.0 2016 Meets | | |
| LEED (version 4) | | | | | |
| Potential direct or indirect contribution to following | Materials and Resources | Building product disclosure and optimisation - EPD up to 2 po | | | |
| categories and credits: | | Building product disclosure materials - up to 1 point | e and optimisation - sourcing of raw | | |
| | | Construction and demolitic | on waste management up to 2 points | | |
| | Indoor environmental quality | Low emitting materials up to 3 points | | | |
| | . , | Acoustic performance up to 1 point | | | |
| Forbo design principles (Redu | ce, Recycle, Reuse, Renew) | | | | |
| Reduce | Investment in an extruder has reduced our bitumen usage by 50%. | | | | |
| Reuse | Yarn ends are rewound and used in the production of new Tessera Carpet tiles. Cutting waste and imperfect tiles can be reprocessed and turned into backing at our Bamber Bridge plant – creating a closed loop process. All Tessera samples can be returned allowing them to be reused or recycled, reducing the need for virgin material. | | | | |
| Recycle | Fillers and compounds all contain recycled materials. All Tessera carpet tiles made in the UK contain at least 50% recycled content by weight. | | | | |
| Renew | All Tessera carpet tiles manufactured at Bamber Bridge are made with 100% renewable energy. (Electricity and biogas). | | | | |