



Installation Method



Non Directional

All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see www.interface.com/disclaimer.

Product Composure **Color** 303021 Deliberate **Backing** GRAPHLEX

Product Specifications

| | |
|----------------------|-----------------------------|
| Product Number | 1034512505 |
| Product Construction | Tufted Textured Loop |
| Yarn System | Post-Consumer Content Nylon |
| Yarn Manufacturer | Universal |
| Dye Method | 100% Solution Dyed |

| | Imperial | Metric |
|--------------------|---|--|
| Tufted Yarn Weight | 18 oz/yd ² , 17 oz/yd ² | 610 g/m ² , 576 g/m ² , 0 g/m ² |
| Machine Gauge | 1/12 in | 47.2 ends/10cm |
| Pile Height | 0.17 in | 4.2 mm |
| Pile Thickness | 0.095 in | 2.4 mm |
| Stitches | 9.3 /in | 36.7 ends/10cm, 0 ends/10cm |
| Pile Density | 6,821 oz/yd ³ | 252,921 g/m ³ |
| Size | 19.69 in x 19.69 in | 50cm x 50cm |

Performance Specifications

| | |
|--------------------------|---|
| Flooring Radiant Panel | (ASTM E-648) Passes |
| Smoke Density | (ASTM E 662) ≤ 450 |
| Flammability | Passes Methenamine Pill Test (DOC-FF1-70) |
| Lightfastness | >7 (ISO 105/B02) |
| Static | (AATCC - 134) < 3.0 KV |
| Dimensional Stability | AACHEN Din 54318 < 0.10% |
| Traffic Classification | Heavy |
| Fiber Modification Ratio | 1.7 to 1.9 |

Health + Environmental Specifications

| | |
|-------------------------------------|---|
| Full Life Cycle Carbon Emissions | Certified Carbon Neutral Floors™ |
| Total Recycled Content | 75% |
| Recycled Content (Pre Consumer) | 70% |
| Recycled Content (Post Consumer) | 5% |
| Indoor Air Quality | Green Label Plus |
| Material Composition | Free of Added Heavy Metals, Ortho Phthalates, Formaldehyde, Fluorinated Chemicals (PFAS), and Halogenated Flame Retardants. |
| Disclosure of Environmental Impacts | Environmental Product Declaration |
| Environmental Certifications | , |
| LEED v4 | Contributes to multiple IEQ and MR credits |
| End of Life | Carpet to Carpet Recycling through ReEntry® |

Technical Information

| | |
|--|--|
| Installation | Interface Installation Guidelines |
| Maintenance | Recommended Interface Maintenance Guidelines |
| Reclamation | Recyclable through ReEntry® - Call 1.888.733.6873 (U.S.) / 1.866.398.3191 (Canada) |
| Warranty | 15 Year Standard Carpet Warranty |
| Installation Method | Non Directional |
| Standard Backing | GRAPHLEX |
| Backing Options (Learn more) | CQuest™Bio, GRAPHLEX, ReadyBac™, CUSHIONBAC |
| Tile Size Options | 50cm x 50cm, 50cm X 50cm |
| Manufacturing Location | ISO 9001 & 14001 Certified facilities in Europe |