



	Standard Ref	Tiles
Product name		Eden
Construction	ISO 2424	1/10th Gauge
Fibre type	ISO 2076	100% Polypropylene
Primary Backing	ISO 2424	Non-woven Polyester
Secondary Backing	ISO 2424	Bitumen
Stitch Rate		43/10cm
Backing Weight		2,500gm/m <sup>2</sup>
Precoat Weight		810gm/m <sup>2</sup>
Total Carpet Weight	BS 4223	4,180gm/m <sup>2</sup>
Total Thickness	BS 4223	5.9mm $\pm$ 10%
Colour Range		12
Tile Size	BS 4939/ISO 3416	50cm x 50cm
Tiles per box	BS ISO 2094	20 or 5 square metres



## Installation


All aspects of sub floor preparation and flooring installation must be carried out in accordance with BS5325:2001 Code of Practice for installation of Textile Floorcoverings. Sheet carpet should be fully adhered with approved adhesives. The products should be allowed to acclimatise for 24 hours at room temperature (15-20°C) prior to installation. We recommend that the tiles are installed by turning alternate tiles through 90° to obtain a chequerboard pattern and should be adhered with approved adhesives. During both planning and installation, consideration must be given to batch matching and pile direction. For further information contact the Rawson Carpet Sales Team.

## Maintenance

A regular maintenance programme is always recommended. Use a suction type of vacuum cleaner for daily maintenance. Periodic shampooing and cleaning by a professional cleaning company should be carried out to keep floorcoverings in good condition. Do not use petrol or similar solvents on these products. It is strongly recommended that to prevent excessive flattening, use cups and pads under heavy furniture and chair mats under castor chairs. With tile products, traffic paths can be avoided by interchanging the tiles as necessary.

## Environmental information

- Rawson products achieve either A or A+ across BREEAM defined building regulations. For specific rating, please refer to [www.breeam.co.uk](http://www.breeam.co.uk)
- All Rawson carpet sheet and tile are made in the UK.
- Wherever possible, raw materials are sourced in the UK.
- Continuous assessment and improvement of manufacturing process is implemented to minimise use of raw materials/power.



Recommended  
tile layout

# Technical specification sheet:



**RAWSON**  
CARPET SOLUTIONS

All weights and thickness quoted +/- 10%. Due to batch to batch variation, production material may vary in colour from that shown on the sample card.