

540 EUROSAFE SPECIAL

Floor covering adhesive with a high initial grab.



Product Typification

Basis	: Superior acrylic dispersion.
Colour	: Beige.
Consistency	: Thick liquid.

- Non-flammable
- Easy and safe to apply
- High initial adhesion strength and final bond strength
- Favourable spreading capacity
- Roller-castor-chair resistant

Performances

Consumption	: 250 - 350 g/m ² , depending on the back of the floor covering and condition of the subfloor.
Flammability	: Non-flammable.
Specific weight	: 1.32 kg/l.

Application

For installing:

- PVC floor covering in sheets and tiles
- cushion vinyl
- PVC backed carpet
- rubber floor covering in sheets and tiles with a smooth back
- polyolefin floor covering.

Working Process

Storage	: Store cool and free from frost.
Tools	: Eurocol spreader no. 852/A2. Type of spreader depends on the floor covering.
Open time	: 60 minutes.*
Latency	: 10 - 20 minutes.*
Drying time	: 48 hours.*
Shelf Life	: 12 months, in unopened packaging.

* The mentioned values have been established in our laboratory and must be considered as guidelines in view of possible variations in climatic circumstances, subfloor compositions and layer thickness.

Substrate:

- 540 Eurosafespecial is suitable for any type of subfloor that has a good tensile and compression strength. The subfloor should also be even,

- clean, permanently dry and free from grease and dirt, according to the requirements of BS 8203 or DIN 18 365.
- When installing on impervious subfloors apply a 2 mm layer of levelling compound.
 - In advance always seek our technical data sheets. In doubt about the application ask for technical advice.

User manual:

Working conditions:

Required surrounding temperature : 18 - 23 °C.

Temperature for material and subfloor : min. 15° - max. 20 °C.

Relative humidity : 40 - 80%.

Directions for use:

- Apply the adhesive with a fine-notched adhesive spreader (Eurocol spreader no. 852/A2). Type of spreader depends on the floor covering and condition of the subfloor.
- When installing impervious floor covering keep a waiting time of approx. 15 minutes.
- Prevent that the adhesive strips show through and avoid impressions caused by a concentrated force on the floor covering by rolling the adhesive strips immediately after application of the adhesive (A2 spreader). In this way the application time of the floor covering is reduced tot max. 10 minutes. Thereafter apply the floor covering as soon as possible and roll carefully. An extended open time can lead to seams and disconnection. Before application contact the floor covering manufacturer or our technical department.
- When installing polyolefin or polyurethane floor covering, wait until the top of the adhesive stripes have dried transparent.
- Roll the floor covering carefully. Sheet-ends and longitudinal joints are to be pressed firmly.
- Rolling and pressing should be repeated after approx. 30 minutes.
- Remove fresh adhesive spots immediately with water.

Underfloor heating systems:

540 Eurosafe Special can be applied on underfloor heating systems. The startprotocol of the floorheating needs to be completely executed in accordance with the directives of the supplier. Turn off the heater 24 hours before application. Do not heat again until at least 48 hours after installation, in steps of maximum 5 °C water temperature per day.

Contains methylchloroisothiazolinone and methylisothiazolinone (3:1). May produce an allergic reaction.

Quality and guarantee



Environment and health

Hazard Class	:	None.
Safety and environment	:	Safety data sheets of Forbo Eurocol products according to EEG-guideline 91/155.
MSDS	:	Available on request.

Articles

Article	Definition	Packaging	EAN-code
540	Eurosafe Special	13 kg Bucket	8 710345 540018