

# Granit Multisafe

## Datasheet

Classification	Norm	Tarkett Value
Product type	ISO 10581	Homogeneous vinyl floor covering
Binder content	ISO 10581	Type I
Commercial classification	ISO 10874	31 Moderate
Characteristics	Norm	Tarkett Value
Total thickness	ISO 24346	2.50 mm
Wear layer thickness	ISO 24340	2 mm
Total weight	ISO 23997	3010 g/m <sup>2</sup>
Performance for CE Marking	Norm	Tarkett Value
Declaration of Performance	EN 14041	0019-0034-DoP-2013-07
Reaction to fire	EN 13501-1	Bfl-s1
Reaction to fire	EN ISO 9239-1	≥ 8 kW/m <sup>2</sup>
Reaction to fire	EN ISO 11925-2	Pass
Electrical Propensity	EN 1815	Antistatic (≤ 2 kV)
Thermal resistance (m <sup>2</sup> K/W)	EN 12667	0,010 m <sup>2</sup> •K/W
Slip resistance	EN 13893	Class DS (μ ≥ 0.30)
Technical Performance	Norm	Tarkett Value
Marine Equipment	IMO 2010 FTP Code part 2 and 5	Approved
Residual indentation	EN ISO 24343-1	≤ 0.10 mm Best measured value: 0,02 mm
Slip resistance	DIN 51130	R10
Slip Resistance	BS 7976-2	Low risk of slip
Slip resistance	DIN 51097	C
Curl resultant to heat	EN ISO 23999	≤  8  mm
Colour fastness to light	ISO 105-B02	≥ 7
Dimensional stability	EN ISO 23999	Average Measured Value : ≤ 0.40 %
Chemical resistance	ISO 26987	Good resistance
Bacteria Resistance	ISO 846 Part C	Does not promote growth
Underfloor heating		Suitable (subfloor temperature maximum 27°C)
Wetroom approval	EN 13553 Annex A	Watertight
Seam Strength Average Value	EN 684	≥ 400 N/50mm
Sustainability, Environment & Indoor Air Quality	Norm	Tarkett Value
Recyclability through ReStart®		Recyclable
Total recycled content		25.5 %
Carbon Footprint (Cradle-to-Gate, EPD Modules A1-A3)		5.26 kg CO <sub>2</sub> e /m <sup>2</sup>
Total Carbon Footprint (EPD Modules A-D, incl. recycling scenario)		3.60 kg CO <sub>2</sub> e /m <sup>2</sup> /year
TVOC emissions after 28 days	EN 16516	Platinum (≤ 10 μg/m <sup>3</sup> )
Formaldehyde emission		E1
Dimensions and designs		
Roll		Roll 2x25m
Number of designs available		16



The above information is subject to modification for the benefit of further improvement (08/02/2023). According to the European Regulation N°305/2011 for CE Marking, the Declarations of Performance are available on our website <https://www.tarkett.com> Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for the instructions.