

HarlemTex - Technical Information

| | | |
|------------------------------|---------------------------|---------------------------------|
| Domestic wear warranty | | 7 years |
| Classification | EN ISO 10874 | Class 21 |
| Binder content | ISO 11638 | Type I |
| Thickness | ISO 24346 | 2.5mm |
| Wear layer | ISO 24340 | 0.15mm |
| Total weight | ISO 23997 | 1440 g/m ² |
| Roll widths | | 2, 3 & 4m |
| Standard roll length | | 25m |
| Slip resistance | EN 13893 | ≥ 0.50 (DS) |
| Slip resistance | DIN 51130 | R10 |
| Reaction to fire | EN 13501-1 | Cfl-s1 |
| Impact sound reduction | EN ISO 717-2 | 17 dB |
| Electrostatical propensity | EN 1815 | < 2 kV |
| Dimensional stability | EN ISO 23999 | ≥ 0.15% |
| Residual indentation | EN ISO 24343-1 | ≤ 0.35 |
| Underfloor heating | | Suitable (max 27°C) |
| Thermal resistance | ISO 10456 / EN 12524-1 | 0.04 m ² K/W |
| Colour fastness | ISO 105-B02 | ≥ 6 |
| Chemical resistance | EN ISO 26987 | Not affected |
| TVOC emissions after 28 days | EN 16516 | Gold (≤ 100 µg/m ³) |
| Recycled content | | 20% |
| Surface treatment | | PU (Extreme Protection) |



Phthalate Free



CERTIFIED BY
SCS Global Services



INDOOR
EMISSIONS