

Product Heuga 727 **Backing** CQuest™Bio

Product Specifications

| | |
|----------------------|---|
| Product Construction | Tufted Plain Level Loop Pile |
| Yarn System | 100% Recycled Solution Dyed Nylon |
| Standard Backing | CQuest™Bio |
| Packaging | 5m2 Box |
| Optional Backings | ReCushion Bac® CQuest™Bio SONE CQuest™Bio SONE+ |

More Product Specifications

| | |
|--------------------------|------------------------------|
| Pile Yarn Weight | 535.00 g/m ² ± 5% |
| Total Weight | 3,704 g/m ² ± 5% |
| Pile Height | 2.50 mm +15% / - 10% |
| Total Thickness | 5.8 mm ±0.5mm |
| Gauge - Ends per 10 cm | 1/10 - 39.4 |
| Tufts per m ² | 157600 /m ² ±5% |


Performance Specifications

| | |
|--|---|
| Wear Classification | EN 1307 33 Heavy Contract |
| Castor Chair Rating | BS-EN 985 r ≥ 2.4 |
| Flammability | (EN ISO 9239-1) Euroclass Cfl-s1 (EN 13501-1) |
| Light Fastness | ≥5 (ISO 105-B02) |
| Light Reflectance Value (LRV-L) | 31.70 |
| Light Reflectance Value (LRV-Y) | 6.90 |
| Dimensional Stability | ≤0.2% (ISO 2551/EN 986) |
| Impact Sound Insulation ΔLw EN ISO 10140-3 | 25 dB |
| Rating of Sound Absorption (αw) EN ISO 11654 | 0.15 |
| Sound Absorption (αs)EN ISO 354 at 125 Hz | 0.02 |
| Sound Absorption (αs)EN ISO 354 at 250 Hz | 0.03 |
| Sound Absorption (αs)EN ISO 354 at 500 Hz | 0.06 |
| Sound Absorption (αs)EN ISO 354 at 1000 Hz | 0.17 |
| Sound Absorption (αs)EN ISO 354 at 2000 Hz | 0.26 |
| Sound Absorption (αs)EN ISO 354 at 4000 Hz | 0.34 |

Environmental Specifications

| | |
|------------------------|------|
| Total Recycled Content | 83 % |
|------------------------|------|

Installation Method



Quarter turn Monolithic

All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see www.interface.com/disclaimer.

| | |
|------------------------------------|---|
| Pre-Consumer (Total) | 76.00 % |
| Post-Consumer (Total) | 7.00 % |
| Yarn Recycled Content | 100.00 % |
| Pre-Consumer (Yarn) | 50.00 % |
| Post-Consumer (Yarn) | 50.00 % |
| Total Bio Based Content | 10.71 % |
| Total Recycled & Bio Based Content | 93.71 % |
| Indoor Air Quality | GLP 100209 M1 Emission Certification -CQB |
| HQE (France) | View Potential HQE Contribution |
| DGNB (Germany) | View Potential DGNB Contribution |
| Embodied Carbon (Cradle to Gate) | 2.93 kg CO ₂ eq./m ² |
| Full Life Cycle Carbon | Certified Carbon Neutral Floors™ |
| Installation Waste | Quarter turn – 3-4% Monolithic – 3-4% |
| TacTiles® | Optimised for glue-free installation with TacTiles® connectors with virtually zero VOCs |
| Recycling | Can be returned through the Interface ReEntry scheme and be reused as raw material in new carpet tiles. |
| ReUse | Can be cleaned and reused in a non-critical location to extend its useful life. |
| Waste to Energy | Can be incinerated in appropriate waste to energy plant. |
| Technical Information | |
| Installation | See recommended Interface installation guidelines |
| Maintenance | See recommended Interface maintenance guidelines |
| Warranty | 15 years |
| Manufacturing Location | ISO 9001, 14001 & 45001 Certified Facilities in Europe |