



## Installation Method



Monolithic    Non Directional    Quarter Turn



Ashlar    Brick

Interface European Manufacturing BV reserve the right to change or modify specifications.

Product Textured Stones    Colour A00309 Medium Concrete

## Product Specifications

|                      |                                                                               |
|----------------------|-------------------------------------------------------------------------------|
| Product Number       | A003                                                                          |
| Product Construction | High Performance Luxury Vinyl Tile Contains 39% Pre-Consumer Recycled Content |
| Finish               | Ceramor™ - UV Stabilised Ceramic Bead Coating                                 |
| Wear Layer Thickness | (EN ISO 24340) 0.55 mm                                                        |
| Total Thickness      | (EN ISO 24346) 4.5mm                                                          |
| Total Weight         | (EN ISO 23997) 6880 g/m²                                                      |
| Size – Packaging     | 50 x 50 cm – 2.5 m² Box                                                       |
| Backing              | Sound Choice™ Acoustic Backing                                                |

## Performance Specifications

|                                                           |                                                                |               |
|-----------------------------------------------------------|----------------------------------------------------------------|---------------|
| Wear Classification                                       | EN ISO 10874 33 Heavy Commercial / 42 General Light Industrial |               |
| CE Declaration Of Performance                             | <a href="#">DOP PBRG-AHCK3R</a>                                |               |
| UKCA Declaration of Performance                           | <a href="#">DOP PBRG-AHCK3R</a>                                |               |
| Castor Chair Rating                                       | (ISO 4918 / EN425) Pass                                        |               |
| Flammability                                              | (EN ISO 9239-1) Euroclass Bfl-s1 (EN 13501-1)                  |               |
| Light Fastness                                            | ≥7 (ISO 105-B02)                                               |               |
| Light Reflectance Value (LRV)                             | LRV – L value                                                  | LRV – Y value |
|                                                           | 51.26                                                          | 19.49         |
| Dimensional Stability                                     | (ISO 23999) ≤ 0.25%                                            |               |
| Curling                                                   | (ISO 23999) ≤ 2 mm                                             |               |
| Flexibility                                               | (EN ISO 24344) Method A - Pass.                                |               |
| Abrasion Resistance                                       | (EN 660-2) Group T                                             |               |
| Residual Indentation                                      | mm(EN ISO 24343-1) ≤ 0.2                                       |               |
| Determination of Anti-Slip                                | (DIN 51130) R10                                                |               |
| Chemical Resistance                                       | (EN ISO 26987) Very Good                                       |               |
| Impact Sound Insulation ΔL <sub>w</sub><br>EN ISO 10140-3 | 16 dB                                                          |               |

## Environmental Specifications

|                                       |                                                                                                                                                 |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|
| Total Recycled Content                | 39%                                                                                                                                             |
| Indoor Air Quality                    | French A+<br><a href="#">Indoor Air Comfort GOLD®</a><br><a href="#">M1 Emission Certification - LVT</a><br><a href="#">LVT Greenguard Gold</a> |
| Potential Green Building Contribution |                                                                                                                                                 |
| Environmental Product Declaration     | <a href="#">MR-ULE-EPD-INF-20170001-EN</a>                                                                                                      |
| Full Life Cycle Carbon Footprint      | According to EPD or EPD calculation method                                                                                                      |
| Embodied Carbon (Cradle to Gate)      | 12.3 kg CO <sub>2</sub> eq./m²                                                                                                                  |
| Full Life Cycle Carbon                | Certified Carbon Neutral Floors™                                                                                                                |
| End of Life Options                   |                                                                                                                                                 |
| ReUse                                 | Can be cleaned and reused in a non-critical location to extend its useful life.                                                                 |
| Fully Recyclable                      | Can be recycled into carpet tile backing.                                                                                                       |
| Material Composition                  | Free of Ortho Phthalates                                                                                                                        |

## Technical Information

|              |                                                             |
|--------------|-------------------------------------------------------------|
| Installation | <a href="#">See recommended LVT installation guidelines</a> |
| Maintenance  | <a href="#">See recommended LVT maintenance guidelines</a>  |
| Warranty     | <a href="#">15 years LVT</a>                                |

## Performance Qualifications



## Certifications

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <div><div>CE</div><div>17</div><div>Interface European Manufacturing B.V.<br/>Industrielaan 15<br/>3925 BD<br/>Scherpenzeel<br/>The Netherlands</div><div>DOP PBRG - AHCK3R</div><div>EN 14041:2004<br/>Notified Body - 0321</div><div>Resilient floor covering for internal use.<br/>Classification Class 33/42 (EN ISO 10874)<br/>Reaction to fire Class Bfl-s1 (see EN 14041, clause 4.1)<br/>Slip resistance Class DS (See EN 14041, clause 4.5)<br/>Formaldehyde E1 (see EN 14041, clause 4.3)<br/>Anti-static &lt; 2.0kV (See EN14041, clause 4.6.1)</div><div>www.interface.com/lvt-emea</div></div> | <div><div>UK<br/>CA</div><div>21</div><div>Interface European Manufacturing B.V.<br/>Industrielaan 15<br/>3925 BD<br/>Scherpenzeel<br/>The Netherlands</div><div>DOP PBRG - AHCK3R</div><div>EN 14041:2004<br/>Notified Body - 0321</div><div>Resilient floor covering for internal use.<br/>Classification Class 33/42 (EN ISO 10874)<br/>Reaction to fire Class Bfl-s1 (see EN 14041, clause 4.1)<br/>Slip resistance Class DS (See EN 14041, clause 4.5)<br/>Formaldehyde E1 (see EN 14041, clause 4.3)<br/>Anti-static &lt; 2.0kV (See EN14041, clause 4.6.1)</div><div>www.interface.com/lvt-emea</div></div> |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

