

QUALITY
ORDER CODE

DATE: **4/06/2018**
REPLACES: 2/05/2018

WIDTH (±) cm
TYPE
GAUGE AND TYPE
TEXTURING
DYEING/PRINT METHOD

PILE COMPOSITION
FIBRE BRAND
WOOLMARK
MOTHPROOF

PRIMARY BACKING

SECONDARY BACKING

PILE WEIGHT (±) gr/m²
TOTAL WEIGHT (± 15%) gr/m²

EFFECTIVE PILE HEIGHT (±) mm
TOTAL HEIGHT (±) mm
NUMBER OF KNOTS (±) m²
STITCHES OVER WIDTH (±) / 10 cm
STITCHES OVER LENGTH (±) / 10 cm

REPEAT TUFTING DESIGN L/W (±) mm
REPEAT PRINTING DESIGN L/W (±) mm

ROLL LENGTH (±) m
PILE IN/OUT

LANO CLASSIFICATION

BEDROOM
LIVING ROOM
OFFICE
CASTOR ROLLCHAIRS DOMESTIC USE
CASTOR ROLLCHAIRS PROFESSIONAL USE
STAIRS DOMESTIC USE
STAIRS PROFESSIONAL USE
ELECTROSTATIC BEHAVIOUR
UNDERFLOOR HEATING
BATH ROOM
NON-FRAY
PERSONAL COMPUTER

PRODIS-NUMBER

GUT-NUMBER
DIBT

UPEC n°
CLASSIFICATION

HQE
EN 1307

ADDITIONAL CHARACTERISTICS EN 1307

LUXURY CLASS

FIRE RESISTANCE EUROPE

EN 13501-1

FIRE RESISTANCE UK

BS 4790

LANO CLASSIFICATION
CLASSIFICATION BS7131

PASHMINA LUXE SMB
PAL

± 400 & 500
COLLECTION
1/10" CUT PILE

SOLUTION DYED

PES

WOVEN

SMART BACK

± 2.200
± 3.180

± 12,5
± 14,5
± 189.120
± 39,40
± 48,00

±
±

± 25
PILE IN

✓
✓

✓

Cl. 22
Domestic General/Medium



LC5



Bfl-s1




LOW RADIUS

Extra Heavy Domestic

QUALITY

DIMENSIONAL STABILITY			EN 986	≤
IMPACT SOUND INSULATION	(±) dB		ISO 140/8	± 25
SOUND ABSORPTION	(±)	α_s	ISO 354 - 125 Hz	±
	(±)		250Hz	±
	(±)		500Hz	±
	(±)		1000Hz	±
	(±)		2000Hz	±
	(±)		4000Hz	±
SOUND ABSORPTION	(±)	α_w	EN ISO 11654	±
THERMAL RETENTION	(±) m ² /KW		ISO 8302	±
TOG rating	(±)			± 1,7
PERMANENTLY ANTISTATIC	(±) volt		ISO 6356	≤
SURFACE RESISTANCE RoT	(±) ohm		ISO 10965	≤
SURFACE RESISTANCE RdT	(±) ohm		ISO 10965	≤
LIGHTFASTNESS			ISO 105-B02	≥ 5
RUBBINGFASTNESS DRY			ISO 105 X12	≥ 3-4
RUBBINGFASTNESS WET			ISO 105 X12	≥ 3
WATERFASTNESS CHANGE IN COLOUR			ISO 105-E01	≥ 3-4
WATERFASTNESS STAINING			ISO 105-E01	≥ 2-3

PASHMINA LUXE SMB



**ALL-OVER STICK DOWN
WITH EC1 APPROVED ADHESIVE**

LABEL CE

RECOMMENDED INSTALLATION

MANUFACTURING TOLERANCE

(±) These details are approximate. Due to method of manufacture perfect pattern and/or colour matching cannot be guaranteed. In cut-pile carpeting, in rare cases, shading/pile reversal may occur without affecting its fitness for use. Shading/pile reversal can not be considered as a manufacturing or a material defect and will not affect the durability of the carpet.

AVAILABLE FROM

AVAILABLE FROM

COLOURS

SMB 400	PAL	SMB 500
250	MAGNOLIA	250
270	ALMOND	270
280	HAVANNA	280
420	CORNSTALK	420
430	BAMBOO MAT	430
440	IVORY	440
450	SAND	450
810	CHARCOAL	810
820	SLATE	820
830	ASH	830
840	MOONSHINE	840
860	GRANITE	860

SMB 400	PAL	SMB 500

