


Technical specification sheet:

Patio



RAWSON
CARPET SOLUTIONS

	Standard Ref	Sheet
Product name		Patio - UV Stabilised
Product description		Outdoor Suitable Carpet Sheet
Fibre type		100% polypropylene
Fibre weight (+/- 10%)		1000g/m sq
Total weight (+/- 10%)		1200g/m sq
Total thickness (mm) (+/- 10%)		9.5
Dimensions		2mx30m
Light reflectance value	BS 8493:2008	In house
Static loading	BS 4939/ISO 3416	Pass
Dynamic loading	BS ISO 2094	Pass
Lisson Tretrad	BS EN 1963-A/	Grade 1
Colour fastness: light	BS EN ISO 105-B02	Grade 6
Colour fastness: shampoo	BS 1006-UK-TB	Grade 4/5
Colour fastness: rub	BS EN 105-X12	Grade 4/5
Colour fastness: water	BS EN 105-E01	Grade 5
Hot metal nut	BS 4790	Low radius char
Castor chair rating	BS EN 985A	Pass
Electrical Resistance	IBM / ICL Electrodes	Pass H 4.24 X 107, V 2 172 X 107
Euroclass	BS EN ISO 11925-2	
Dimensional stability to heat	BS 4682 Part 3	Tested
Dimensional stability to water	BS 4682 Part 4	Tested
Dimensional stability ambient	BS4682 Part 2	Tested
Body Voltage test	BS EN 1815	Pass



Installation

All aspects of sub floor preparation and flooring installation must be carried out in accordance with BS5325:2001 Code of Practice for installation of Textile Floorcoverings. Please see full adhesive products matrix online. Sheet and tile carpet should be fully adhered with approved adhesives.

All products should be allowed to acclimatise to room condition for 24 hours at room temperature (15-20°C) prior to installation.

We recommend that the tiles are installed by turning alternate tiles through 90° to obtain a chequerboard pattern.

During both planning and installation, consideration must be given to batch matching and pile direction. For further information contact the Rawson Carpet Sales Team.

Maintenance

Regular maintenance programmes are highly recommended. Use a suction type of vacuum cleaner for daily maintenance. For best results, periodic shampooing and cleaning by a professional cleaning company should be carried out. Do not use petrol or similar solvents on these products. It is strongly recommended that to prevent excessive flattening, use cups and pads under heavy furniture and chair mats under castor chairs. With tile products, traffic paths can be avoided by interchanging the tiles as necessary.

Environmental information

- Rawson products achieve either A or A+ across BREEAM defined building regulations. For specific rating, please refer to www.breeam.co.uk
- All Rawson carpet/carpet tile ranges are made in the UK.
- Wherever possible, raw materials are sourced locally.
- Continuous assessment and improvement of manufacturing process is implemented to minimise use of raw materials/power.
- Where ever possible, manufacturing waste is recycled

Technical specification sheet:

production material may vary in colour from that shown on the sample card.

