

## PRIMO CHOICE CONSTRUCTION SPECIFICATION

		<b>SUPER</b>	<b>ELITE</b>
CONSTRUCTION		Tufted Cut Pile Carpet	Tufted Cut Pile Carpet
PILE CONTENT	BS4407	100% Excellon PP	100% Excellon PP
WIDTH	BS3655	4 metre & 5 metre	4 metre & 5 metre
SUITABILITY		Heavy Domestic	Extra Heavy Domestic / Medium Contract
ROLL SIZE		Standard 25m or 30m (Special sizes can be supplied, please allow extra time for delivery)	Standard 25m or 30m (Special sizes can be supplied, please allow extra time for delivery)
PRIMARY BACKING		Woven Polypropylene	Woven Polypropylene
SECONDARY BACKING		Woven Secondary	Woven Secondary
PILE HEIGHT	BS 4223/ISO 8543	6.7 mm	8.6 mm
TUFT DENSITY	BS 4223/ISO 8543	139,500 tufts/m <sup>2</sup>	162,750 tufts/m <sup>2</sup>
PILE WEIGHT	BS 4223/ISO 8543	1152 gms/m <sup>2</sup> (34 oz/yd <sup>2</sup> )	1627 gms/m <sup>2</sup> (48 oz/yd <sup>2</sup> )
TOTAL CARPET WEIGHT	BS 4223/ISO 8543	1899 gms/m <sup>2</sup>	2407 gms/m <sup>2</sup>
TOTAL CARPET THICKNESS	BS 4051/ISO 1765	10.2 mm	11.9 mm
WIRA ABRASION TEST		Exceeds 50,000 rubs	Exceeds 50,000 rubs
STATIC LOADING		18% Thickness Loss after 24 hrs recovery	16.8% Thickness Loss after 24 hrs recovery
DYNAMIC LOADING		41.5% Thickness Loss after 1,000 impacts	31.3% Thickness Loss after 1,000 impacts
TUFT ANCHORAGE		Above 1.0kg	Above 1.0kg
<b>FLAMMABILITY</b>			
METHENAMINE PILL TEST		Pass	Pass
<b>COLOUR FASTNESS</b>			
LIGHT FASTNESS		BS 1006 above Grade 4/5 on all colours	BS 1006 above Grade 4/5 on all colours
WET FASTNESS		BS 1006 above Grade 5 on all colours	BS 1006 above Grade 5 on all colours
SHAMPOO FASTNESS		BS 1006 above Grade 5 on all colours	BS 1006 above Grade 5 on all colours
BIOLOGICAL ATTACK		Insect and rot proof	Insect and rot proof
THERMAL RESISTANCE (Tog Value)	BS 4745/ISO 5085-1	1.0 Tog	1.2 Tog

All specifications are subject to normal manufacturing tolerances.

### GENERAL INFORMATION

#### Installation

In all contract locations an 'all over' stick down method is recommended to BS 5325 (1983). If underlay is required it should be of a firm and unyielding type and where installed in larger contract areas the carpet should be power stretched. If exact colour matching is required for a quantity order, please state this point clearly when ordering.

#### Maintenance

To maintain your carpet's appearance it is recommended that it is vacuumed at least three times per week, to remove particles of dirt and dust. An upright vacuum with beater bar and brush is recommended for use with cut pile carpets. Please note, over time, regular foot traffic will flatten the pile surface in the main walkways, causing areas of differential wear. These areas will appear lighter or shaded in comparison to the less frequently used parts. This shading / tracking or flattening happens to all carpets with a pile surface and as such is not accepted as the basis for any complaint. Similarly Pile Reversal (or watermarking) is a phenomenon that can affect all cut pile carpets and as such is not accepted as a manufacturing fault.

#### Matching

This sample may not be from the same production batch as current stock and therefore should be used as a guide and not as an exact match. Equally matching between 5 metre and 4 metre widths cannot be guaranteed.

#### Important

Minimum order length is 1.5 metres.

August 2012



#### GREENWOOD & COOPE LTD

BROOKHOUSE MILL, GREENMOUNT, BURY, LANCASHIRE BL8 4HR TEL: 01204 881234 FAX: 01204 887722  
E-MAIL: info@cormarcarpets.co.uk WEBSITE: www.cormarcarpets.co.uk

