

CORMAR

CARPET CO

PRIMO CHOICE: TECHNICAL SPECIFICATION



CONSTRUCTION

		SUPER	ELITE
MACHINE GAUGE		Tufted Cut Pile Carpet	Tufted Cut Pile Carpet
PILE HEIGHT	BS 4223/ISO 8543	1/10th Cut Pile	1/10th Cut Pile
TUFT DENSITY	BS 4223/ISO 8543	6.7 mm	8.6 mm
PILE WEIGHT	BS 4223/ISO 8543	139,500 tufts/m ²	162,750 tufts/m ²
		1,152 gms/m ²	1,627 gms/m ²
		34 oz/yd ²	48 oz/yd ²
TOTAL CARPET WEIGHT	BS 4223/ISO 8543	1,899 gms/m ²	2,407 gms/m ²
CARPET THICKNESS	BS 4051/ISO 1765	10.2 mm	11.9 mm
WIDTH	BS	4 & 5 metre	4 & 5 metre
ROLL SIZE		Standard 25m or 30m (Special sizes can be supplied, please allow extra time for delivery)	Standard 25m or 30m (Special sizes can be supplied, please allow extra time for delivery)



COMPOSITION

		SUPER	ELITE
PILE CONTENT	BS 4407	100% Excellon Polypropylene	100% Excellon Polypropylene
PRIMARY BACKING		Woven Polypropylene	Woven Polypropylene
SECONDARY BACKING		Woven Secondary	Woven Secondary



PERFORMANCE

		SUPER	ELITE
SUITABILITY		Heavy Domestic	Extra Heavy Domestic / Medium Contract
WIRA ABRASION TEST		Exceeds 50,000 Rubs	Exceeds 50,000 Rubs
STATIC LOADING		18% Thickness Loss after 24 hrs recovery	16.8% Thickness loss after 24 hrs recovery
DYNAMIC LOADING		41.5% Thickness Loss after 1,000 impacts	31.3% Thickness loss after 1,000 impacts
TUFT ANCHORAGE		Above 1kg	Above 1kg



COLOUR FASTNESS

		SUPER	ELITE
LIGHT FASTNESS	BS 1006	4/5 on all colours	4/5 on all colours
WET FASTNESS	BS 1006	5 on all colours	5 on all colours
SHAMPOO FASTNESS	BS 1006	5 on all colours	5 on all colours



THERMAL VALUE

		SUPER	ELITE
TOG VALUE	BS 4745/ISO 5085-1	1.0 Tog	1.2 Tog



FLAMMABILITY

		SUPER	ELITE
METHENAMINE PILL TEST		CE Pass - Low radius of ignition	Efl Pass - Low radius of ignition



CHEMICAL IMPACT

		SUPER	ELITE
FORMALDEHYDE		CE	E1



BIOLOGICAL ATTACK

		SUPER	ELITE
MOTH / INSECT RESISTANT		Insect and Rot Proof	Insect and Rot Proof

GENERAL INFORMATION

Installation - In all contract locations an 'all-over' stick down method is recommended to BS 5325 (1983). If underlay is required it should be of a firm and unyielding type and where installed in larger contract areas the carpet should be power stretched. For quantity orders requiring colour matching, please state at time of ordering.

Maintenance - To maintain your carpet's appearance it is recommended that it is vacuumed at least three times per week, to remove particles of dirt and dust. An upright vacuum with beater bar and brush is recommended for use with cut pile carpets. Please note, over time, regular foot traffic will flatten the pile surface in the main walkways, causing areas of differential wear.

These areas will appear lighter or shaded in comparison to the less frequently use parts. This shading / tracking or flattening happens to all carpets with a pile surface and as such is not accepted as the basis for any complaint. Similarly Pile Reversal (or watermarking) is a phenomenon that can affect all cut pile carpets and as such is not accepted as a manufacturing fault.

Matching - This sample may not be from the same production batch as current stock and therefore should be used as a guide and not as an exact match. Equally matching between 5 metre and 4 metre widths cannot be guaranteed.

Important - Minimum order length is 1.5 metres.