

Rhinofloor Townhouse

TECHNICAL DATA VINYL FLOORING 2020

| Classification | Norm | Tarkett Value |
|--|------------------------|--|
| Product type | EN ISO 26986 | Expanded (cushioned) poly(vinyl chloride) floor covering |
| Domestic classification | EN ISO 10874 | 32/41 Commercial General/ Industrial Moderate |
| Binder content | ISO 11638 | Type I |
| Technical characteristics | | |
| Total thickness | ISO 24346 | 2.4 mm |
| Wear layer thickness | ISO 24340 | 0,35 mm |
| Total weight | ISO 23997 | 1580 g/m ² |
| Roll Width | | 4 + 2 + 3 m |
| Roll Length | EN ISO 24341 | 25 m |
| Performance for CE Marking | | |
| Declaration of Performance # | EN 14041 | 0004-0023-DOP-2020-01 |
| Reaction to fire | EN 13501-1 | Cfl-s1 |
| Slip resistance | EN 13893 DIN 51130 | ≥ 0,50 (DS) R 10 |
| Electrostatical propensity | EN 1815 | 0,2 |
| Thermal resistance (in m ² ·K/W) | ISO 10456 / EN 12524-1 | 0,03 |
| Formaldehyde emission | EN 717-1 | E1 |
| Technical Performance | | |
| Impact sound reduction - ΔLw | EN ISO 717-2 | 16 dB |
| Residual indentation | ISO 24343-1 | ≤ 0,20 |
| Chemical resistance | ISO 26987 | Not affected |
| Underfloor heating | | Suitable (maximum 27°C) |
| Colour fastness to light | ISO 105-B02 | ≥ 6 |
| Dimensional stability | ISO 23999 | ≤ 0,20 % |
| Castor Chair | ISO 4918 | Ok |
| Sustainability, Environment & Indoor Air Quality | | |
| Recyclable | | Yes |
| French VOC rating | | A+ |
| Phthalate content | | Phthalate-free |
| TVOC emissions after 28 days | EN 16516 | Gold (≤ 100 µg / m ³) |
| Product ID | | |
| Residential warranty (in years) | | 20 |
| Surface treatment | | Extreme Protection |

The above information is subject to modification for the benefit of further improvement (2020-01).



Although the utmost care is taken, the data here given could be imprecise and liable to modifications of a technical nature. Tarkett reserves the right to modify their technical specifications, colours and materials at any moment and without prior notice.