

# Rhinofloor RhinoTex

## TECHNICAL DATA VINYL FLOORING 2020

| Classification                                   | Norm                   | Tarkett Value  |
|--|------------------------|--|
| Product type                                     | EN ISO 26986           | Expanded (cushioned) poly(vinyl chloride) floor covering |
| Domestic classification                          | EN ISO 10874           | 23/41 Domestic Heavy/ Industrial Moderate                |
| Binder content                                   | ISO 11638              | Type I   |
| Technical characteristics                        |                        |  |
| Total thickness                                  | ISO 24346              | 2.8 mm   |
| Wear layer thickness                             | ISO 24340              | 0,35 mm  |
| Total weight                                     | ISO 23997              | 1760 g/m <sup>2</sup>                                    |
| Roll Width                                       |                        | 4 + 2 + 3 m  |
| Roll Length                                      | EN ISO 24341           | 25 m   |
| Performance for CE Marking                       |                        |  |
| Declaration of Performance #                     | EN 14041               | 0004-0016-DOP-2020-01                                    |
| Reaction to fire                                 | EN 13501-1             | Cfl-s1   |
| Slip resistance                                  | EN 13893<br>DIN 51130  | ≥ 0,50 (DS)<br>R 10                                      |
| Electrostatical propensity                       | EN 1815                | ≤ 2 kV   |
| Thermal resistance (in m <sup>2</sup> ·K/W)      | ISO 10456 / EN 12524-1 | 0,04   |
| Formaldehyde emission                            | EN 717-1               | E1   |
| Technical Performance                            |                        |  |
| Impact sound reduction - ΔLw                     | EN ISO 717-2           | 19 dB  |
| Residual indentation                             | ISO 24343-1            | ≤ 0,20   |
| Chemical resistance                              | ISO 26987              | Not affected   |
| Underfloor heating                               |                        | Suitable (maximum 27°C)                                  |
| Colour fastness to light                         | ISO 105-B02            | ≥ 6  |
| Dimensional stability                            | ISO 23999              | ≤ 0,20 %   |
| Castor Chair                                     | ISO 4918               | Ok   |
| Sustainability, Environment & Indoor Air Quality |                        |  |
| French VOC rating                                |                        | A+   |
| Phthalate content                                |                        | Phthalate-free   |
| TVOC emissions after 28 days                     | EN 16516               | Gold (≤ 100 µg / m <sup>3</sup> )                        |
| Product ID                                       |                        |  |
| Residential warranty (in years)                  |                        | 15   |
| Surface treatment                                |                        | Extreme Protection                                       |

The above information is subject to modification for the benefit of further improvement (2020-01).

