



Luxury residential carpet underlay.

Made from a high content of post-consumer fibre waste and vehicle tyre waste.

## SPECIFICATION

Characteristic	Test Method	Result
Nominal thickness		11.00mm
Roll length		7.30m
Roll width		1.37m
M <sup>2</sup> per roll		10.00m <sup>2</sup>
Weight M <sup>2</sup>		ca.2.4kg/m <sup>2</sup>
Nominal roll weight		ca.24kgs
End use specification	BS EN 14499: 2015	HC/U Heavy Contract Use
Work of compression	BS 4098: 1975	99J/m <sup>2</sup>
Retention of work of compression	BS 4098: 1975	68%
Compression after dynamic loading	BS 4098: 1975	3.8mm
Loss in thickness after static loading	ISO 3416	28%
Loss in thickness after dynamic loading	ISO 2094	18.8%
Breaking strength - length	EN ISO 13934-1 <sup>a</sup>	111N
Breaking strength - width	EN ISO 13934-1 <sup>a</sup>	175N
Extension under force - length	EN ISO 13934-1	3.6%
Extension under force - width	EN ISO 13934-1	2.8%
Resistance to cracking	BS EN 14499: 2015	Pass
Flammability - Hot metal nut test	BS 4790: 1987	Low radius of effects of ignition
Tog rating	BS 4745: 2005	2.67
Impact sound improvement	BS EN ISO 10140-3: 2010	34dB

Concern for the future of our planet drives our business. Every Footfall product is made from recycled materials and is itself recyclable.

Footfall Flooring Ltd. | [footfalluk.co.uk](http://footfalluk.co.uk)

**FOOTFALL** for the future