

QUALITY DATE: 10/10/2017
ORDER CODE REPLACES: 24/06/2013

WIDTH (±) cm
TYPE
GAUGE AND TYPE
TEXTURING
DYEING/PRINT METHOD

PILE COMPOSITION
FIBRE BRAND
WOOLMARK
MOTHPROOF

PRIMARY BACKING

SECONDARY BACKING

PILE WEIGHT (±) gr/m²
TOTAL WEIGHT (± 15%) gr/m²

EFFECTIVE PILE HEIGHT (±) mm
TOTAL HEIGHT (±) mm
NUMBER OF KNOTS (±) m²
STITCHES OVER WIDTH (±) / 10 cm
STITCHES OVER LENGTH (±) / 10 cm

REPEAT TUFTING DESIGN L/W (±) mm
REPEAT PRINTING DESIGN L/W (±) mm

ROLL LENGTH (±) m
PILE IN/OUT

CLASSIFICATION

BEDROOM ✓
LIVING ROOM ✓
OFFICE ✓
CASTOR ROLLCHAIRS DOMESTIC USE
CASTOR ROLLCHAIRS PROFESSIONAL USE
STAIRS DOMESTIC USE ✓
STAIRS PROFESSIONAL USE
ELECTROSTATIC BEHAVIOUR
UNDERFLOOR HEATING ✓
BATH ROOM
NON-FRAY
PERSONAL COMPUTER

PRODIS-NUMBER

GUT-NUMBER
DIBT

UPEC n°
CLASSIFICATION

HQE
EN 1307

ADDITIONAL CHARACTERISTICS EN 1307

LUXURY CLASS

FIRE RESISTANCE EUROPE

EN 13501-1

FIRE RESISTANCE UK

BS 4790

CLASSIFICATION
CLASSIFICATION BS7131

VELVET DREAM SB
ZIO

± 400 & 500
COLLECTION (UK/EIRE)
1/10" SAXONY

PIECE DYED

100% TRIEXTA
SMARTSTRAND

WOVEN SYNTHETIC SECONDARY BACKING

± 1.300
± 2.290

± 7,0
± 9,5
± 173.360
± 39,40
± 44,00

±
±

± 50
PILE IN

✓
✓
✓

✓

✓

LC5



Cfl-s1



LOW RADIUS

HEAVY NON-DOMESTIC
Tested on underlay

QUALITY

DIMENSIONAL STABILITY			EN 986	≤
IMPACT SOUND INSULATION	(±) dB		ISO 140/8	± 26
SOUND ABSORPTION	(±)	α _s	ISO 354 - 125 Hz	± 0,01
	(±)		250Hz	± 0,06
	(±)		500Hz	± 0,13
	(±)		1000Hz	± 0,27
	(±)		2000Hz	± 0,52
	(±)		4000Hz	± 0,65
SOUND ABSORPTION	(±)	α _w	EN ISO 11654	± 0,2
THERMAL RETENTION	(±) m ² /KW		ISO 8302	± 0,118
TOG rating	(±)			± 1,18
PERMANENTLY ANTISTATIC	(±) volt		ISO 6356	<
SURFACE RESISTANCE RoT	(±) ohm		ISO 10965	≤
SURFACE RESISTANCE RdT	(±) ohm		ISO 10965	≤
LIGHTFASTNESS			ISO 105-B02	≥ 5-6
RUBBINGFASTNESS DRY			ISO 105 X12	≥ 3-4
RUBBINGFASTNESS WET			ISO 105 X12	≥ 3-4
WATERFASTNESS CHANGE IN COLOUR			ISO 105-E01	≥ 5
WATERFASTNESS STAINING			ISO 105-E01	≥ 4

VELVET DREAM SB



ALL-OVER STICK DOWN
 WITH EC1 APPROVED ADHESIVE

LABEL CE

RECOMMENDED INSTALLATION

MANUFACTURING TOLERANCE

(±) These details are approximate. Due to method of manufacture perfect pattern and/or colour matching cannot be guaranteed. In cut-pile carpeting, in rare cases, shading/pile reversal may occur without affecting its fitness for use. Shading/pile reversal can not be considered as a manufacturing or a material defect and will not affect the durability of the carpet.

COLOURS

AVAILABLE
 FROM

AVAILABLE
 FROM

<u>SB 400</u>	ZIO	<u>SB 500</u>
110	MONARCH	110
141	ROSE	141
150	SOFT COFFEE	150
250	SANDSTONE	250
251	TAUPE SUEDE	251
261	CHOC. MILKSHAKE	261
321	COPPER	321
371	GOLD	371
421	TRUFFLE	421
430	CARAMEL DREAM	430
450	JASMINE	450
541	CHARTREUSE	541
591	MOSS	591
661	CELADON	661
691	SATIN JADE	691
721	BLUE CAPE	721
761	WEDGWOOD	761
800	BLACK INK	800
820	AGED IRON	820
850	MOONSTONE	850
860	GENTLE FAWN	860
870	SNOWFALL	870
880	SOFT STONE	880
890	COTTON WHITE	890

<u>SB 400</u>	ZIO	<u>SB 500</u>



WE RESERVE THE RIGHT TO
 ALTER TECHNICAL SPECIFICATIONS
 WITHOUT PRIOR NOTICE